

OPAL FINESSE - SLIDING DOORS



SUITABLE FOR
RESIDENTIAL,
COMMERCIAL &
RETAIL PROPERTIES




117 MM
TYPICAL SIGHTLINE



250KG
SLIDE

MAXIMUM
SASH WEIGHT
(300KG FOR
LIFT & SLIDE)

U-VALUE **1.6** W/M²K
USING A 1.0 CENTRE PANE



PROVIDING THE WEIGHT
IS BELOW 250KG AND
UNDER 2500MM HIGH,
THERE IS NO MAXIMUM
SASH WIDTH



LIFT & SLIDE
MIN. WIDTH = 702MM
MAX. WIDTH = 3294MM



MAX. SASH
HEIGHT IS
2500 MM

MIN. SLIDING SASH
HEIGHT IS 800MM
(1885MM PAS24)

LIFT & SLIDE
MIN. HEIGHT = 1718MM
MAX. HEIGHT = 2500MM



UP TO 38MM DOUBLE
OR TRIPLE GLAZED
SEALED UNITS.

ALL PROFILES FEATURE
POLYAMIDE BREAK THAT
ENHANCES THERMAL
PROPERTIES



52MM
FRAME
WIDTH

99-184.5
FRAME
DEPTH

AIR
600PA

WIND
2400 PA

WATER
300 PA

PAS
24:2016

DOC. L
COMPLIANT

OPAL FINESSE - SLIDING DOORS

opal@prefixsystems.co.uk | 01792 588254

OPAL

ALUMINIUM WINDOWS AND DOORS