

# OPAL LIVING - WINDOW SYSTEM



SUITABLE FOR  
RESIDENTIAL,  
COMMERCIAL &  
RETAIL PROPERTIES



**85** MM  
TYPICAL SIGHTLINE

**B**

WINDOW  
ENERGY RATING

U-VALUE **1.3** W/M<sup>2</sup>K  
USING CORRECT SEALED UNIT



SIDE HUNG  
MAX WIDTH IS  
**1000** MM



TOP HUNG MAX  
HEIGHT  
**1500** MM

SIDE HUNG  
MAX HEIGHT  
**1400** MM



28 TO 38MM  
DOUBLE OR TRIPLE  
GLAZED UNITS.

ALL PROFILES FEATURE  
POLYAMIDE BREAK THAT  
ENHANCES THERMAL  
PROPERTIES



59&70  
FRAME  
DEPTH

AIR  
600PA

WIND  
2400PA

WATER  
1200PA

PAS  
24:2016\*

DOC. L  
COMPLIANT

\*INTERNALLY BEADED, TOP & SIDE HUNG ONLY

OPAL LIVING - STANDARD WINDOW SYSTEM

opal@prefixsystems.co.uk | 01792 588254

**OPAL**  
ALUMINIUM WINDOWS AND DOORS