

OPAL TILT AND TURN - TILT AND TURN WINDOWS



COMMERICAL WINDOWS
SUITABLE FOR COMMERICAL,
RETAIL, RESIDENTIAL,
PUBLIC, HEALTHCARE &
EDUCATIONAL APPLICATIONS




95 MM
TYPICAL SIGHTLINE



TILT TURN MAX.
WEIGHT OVERALL.

PIVOT MAX. WEIGHT HORIZONTAL = 180KG
PIVOT MAX. WEIGHT VERTICAL = 120KG

U-VALUE **1.4** W/M²K
USING 1.1 SEALED UNIT.
1.1 W/M²K USING TRIPLE
GLAZED 0.6 UNIT



MIN. WIDTH = 402MM
MAX. WIDTH = 1700MM
(AT 1700MM WIDE, MAX.
HEIGHT IS 2100MM)



MIN. HEIGHT = 500MM
MAX. HEIGHT = 2400MM

(AT 2400MM HIGH, MAX
WIDTH IS 1400MM)



GLAZING 13MM-60MM
(SASH)
GLAZING 4MM-51MM
(OUTER FRAME)

ALL PROFILES FEATURE
POLYAMIDE BREAK THAT
ENHANCES THERMAL
PROPERTIES



* WIDTH OF TILT/TURN SASH MUST NOT EXCEED 1 1/2 TIMES THE HEIGHT

FRAME
DEPTH
65MM

WER
A

AIR
600PA

WIND
2400PA

WATER
900PA

PAS
24:2016

DOC. L
COMPLIANT

OPAL TILT & TURN - TILT AND TURN WINDOWS

opal@prefixsystems.co.uk | 01792 588254

OPAL
ALUMINIUM WINDOWS AND DOORS